

Slalom: The gate will remain in the slalom mode.

8.03 Skis

A. Maximum ski width shall not exceed 30% of the length.

B. Any rigid or flexible foot binding may be used including bindings that are firmly attached to the ski or designed to release from the ski in the event of a fall.

1. Bindings may be used that allow the heel of the skier's rear foot to lift off the ski.

2. The specific location in which the binding is positioned on the ski may not move or change during actual skiing.

C. SLALOM AND JUMP SKIS:

1. Any type of **fixed** fins may be used.

2. Devices affixed to the skis intended to control or adjust the skiing characteristics of the ski, for example, wings on a fin, are allowed **as long as they are fixed and do not move or change during actual skiing.**

D. TRICK SKIS:

1. Skis used in the Tricks event shall not have fins.

2. Trick skis with molded rails/grooves less than 1/4" are allowed.

3. A foot pad cemented to the ski as a place for the rear foot is also permitted.

E. With all bindings, fins, etc., installed, the ski must float.

F. Attaching two separate skis together in any manner is prohibited.

8.04 Tow Lines

The Tournament Committee shall furnish tow lines constructed as in 8.04.C below with the lines and handles meeting the following specifications:

A. Weight per foot, maximum = 23 g/m (.250 oz.)
Breaking Load, minimum = 817 kg (1,800 lbs.)
Elongation at 115 kg (250 lbs.) tensile load, 2.6% ± 0.4%
The gauge length shall be set at 5.5 kg (12 lbs.) tensile load

Optional: Light Towlines for B1, B2, G1, G2, W6 and above only

Weight per foot, maximum = 23g/m (.250 oz.)
Breaking Load, minimum = 454 kg (1,000 lbs.)