


PRESSURE CONTROLS

Honeywell

Pressuretrol® L404, L604 Controllers Remanufactured

Provide operating control, automatic or manual reset limit protection for pressure systems up to 300 psi. For use with steam, air, non-combustible gases or other fluids non-corrosive to pressure sensing element.



3

FEATURES:


- Provides dustproof, trouble-free mercury switching.
- Trip-free mechanism on manual reset models so the limit function of the controller cannot be defeated by jamming the reset lever.
- Adjustments are made by screws on top of case.
- Mount using 1/4" NPT female threads on surface mount through base of case.

Action on Pressure Rise	Range	Diff. Adj.	Mfr#	Reman#
Opens	0 - 10 psi	1 - 5 psi	L404A	C355R
Closes	0 - 10 psi	1 - 5 psi	L404B	C355-1R
SPDT	2 - 15 psi	1 - 6 psi	L404F1060	C355-4R
Opens	5 - 150 psi	2 - 16 psi	L404A	C358R
Opens	10 - 150 psi	2 - 16 psi	L404A	C358-1R
SPDT	10 - 150 psi	2 - 16 psi	L404A1195	C358-2R
Opens	2 - 15 psi	Manual reset	L404C1147	C359-10R
Opens	10 - 150 psi	Manual reset	L404C1162	C359-12R

Honeywell

Vaporstat® Controllers

Provide operating or limit control for vacuum and pressure systems. Use stainless steel diaphragm with steam, air or non-combustible fluids not corrosive to stainless steel.



FEATURES:

- Provides dustproof, trouble-free mercury switching.
- Includes siphon loop.
- Mount using 1/4" NPT female fitting on diaphragm assembly or surface mount through back of case.

Action on Pressure Rise	Range	Diff. adj. @ Mid-scale	Mfr#	Reman#
Opens	0 - 1 psi	4 - 16 psi	L408A1132	C359R

NOTE: Remanufactured products available only on exchange for similar defective units.

HEATING CONTROLS