

TYP. GARAGE/LIV. SEPARATION

5/8" 'X' GYP. STRUCT. MEMB.

R-13 unfaced fiberglass batts

5/8" 'X' GYP. BD. CONT. BETWEEN GARAGE & LIVING SPACE

20 MIN. FIRE RATED DOOR W/ WEATHER STRIPPING, THRESHOLD & AUTO CLOSER

TYP. FOUNDATION WALL FURRING

2X4 @ 16" O.C. W/ MIN. R-15 CONTINUOUS OR R-19 CAVITY INSULATION & GYP. BD.

4" Structural slab with welded wire and 1/2" radiant tubing (per structural and mechanical designs)

2" Field applied closed cell spray foam (R-13)

Spray Foam insulation to be cut at approx 45 degrees

4" deep 3/4" Rock

2" Dow "BlueBoard" Installed prior to backfill (R-10)

WINDOW, RE: SWS SCHEDULE

INSUL. SHIM SPACE

MTL. FLASHING

INTERIOR TRIM

2" Field applied closed cell spray foam (R-13)

CONC. SLAB ON COMPACTED FILL, RE: STRUCT.  
CONC. SLAB ON 1/2 MIL POLY V.B. ON 2" POLY ISO INSUL. (R12) ON MIN. 4" COMPACTED CLEAN SAND AND GRAVEL FILL

Concrete slab ledge formed with (2)-2x6

T.O. SLAB RE: PLANS

MATERIAL DIVISION

SLOPE FINISH GRADE AWAY FROM WALL

(2) #5 Rebar top and bottom (typ.)

PROTECTION BOARD DAMPPROOFING W/COVE BASE

CONC. FTG. AND FOUNDATION RE: STRUCT.

4" PERFORATED PVC DRAIN SET IN 3/4" DIA. WASHED GRAVEL, SLOPE TO DRYWELL OR DAYLIGHT

FILTER FABRIC

5 WALL SECTION

A6 1 1/2" = 1'-0"

3 A6

VALLEY D

1 1/2" = 1'-0"

4 A6

RIDGE TR

1 1/2" = 1'-0"